

AP00.20-U-1206Y SERVICE SHEET for Flexible Service System (FSS) (USA) 3.12.02

MODEL 463 MY 2002

## **G-Class Model Year 2002**

USA/CANADA:

System is also known as "Active Service System (ASSYST)" in the Workshop Information System (WIS)

## Model 463



Customer: Repair order number:					
	ork has been by signing below		Type of service last performed On new vehicles start with B		
Technician:					
		Determine need for service:	B A		
	Please define type of service to be	performed here:			
	Current				
	B-Service last performed				
	(Enter 0 if B-Service is performed for Difference	in mi/km:			
		1			
		Difference < 14,000 mi	Difference ≥ 14,000 mi		
		22,000 km	22 000 km		
		A-Service	B-Service		
Determi	ne "Additional work" nee	ded, if any:			
(check if a	applicable)				
at approx	c. every: 60,000 mi/96,0	000 km or 4 years	every: 2 years		
	60,000 mi/96,0	000 km or 5 years	3 years		
			Spark plugs		
			Spark plugs		
Determing of the dispersion of	, an "A-Service" should be pert stance driven since the last "B- ecords), a "B-Service" should be	Service" is <b>less</b> (<) than 14,000 m formed. Service" is <b>greater</b> (≥) than 14,00 e performed.	niles/22 000 km (as determined from Service Booklet or dealer 00 miles/22 000 km (as determined from Service Booklet or		
Additio	nal flat rates apply for procedu	res marked with 😂 🗚 P.			

completed ⊠	A-Service	<u> </u>	O B-Service	Not O.K.	
	Brake test on dynamometer or test drive. Check parking brake and run in according to specifications (observe instructions in Maintenance Manual for vehicles with 4ETS, ESP!) Enter brake values in N: front rear Parking brake	•	⊗		AP42.00-P-4290G
	left				
	right				
	Vehicle passenger compartment				
	Function check				
	Check Tele Aid by pressing SOS button to make test call to Response Center	X	$\otimes$		
	Horn, headlamp flasher, hazard flasher, turn signals	X	$\otimes$		
	Warning/indicator lamps, illumination and interior lighting	X	$\otimes$		
	Exterior lighting incl. headlamps	$\boxtimes$	$\otimes$		
	Windshield wipers, rear window wiper, windshield/rear window washer system, headlamp cleaning system	X	$\otimes$		AP82.30-P-8252G
	Check seat belts for damage and proper function		$\otimes$		AP91.40-P-9150GI
	Lubricate door locks, incl. rear door		$\otimes$		AP72.00-P-7221G
	Reset FSS counter in instrument cluster	$\boxtimes$	$\otimes$		
	Replace dust filter		$\otimes$		AP83.00-P-8381GA
	Check				
	If so equipped: Battery AGM/VRLA, with black housing Check battery condition using "Midtronics MCR 717" Tester. Attach Midtronics MCR 717 Test Report print out here.	$\boxtimes$	⊗		AP54.10-U-5453A
	If so equipped: Battery wet cell, Check acid level, replenish	X	$\otimes$		AP54.10-P-5410A
	Additionally, check battery condition using "Midtronics MCR 717" Tester. Attach Midtronics MCR 717 Test Report print out here.	X	⊗		AP54.10-U-5453A
	Wheels, brakes				
	Remove and reinstall wheels, rotate if necessary.		$\otimes$		AP40.10-P-4050G
	Check front brake pads for lining thickness (remove right front wheel)	$\boxtimes$			AP42.10-P-4251G
	Check brake pads for lining thickness front/rear		$\otimes$		AP42.10-P-4251G
	Check condition/thickness of brake discs front and rear		$\otimes$		AP42.10-P-4251G

completed ⊠	A-Service		B-Service	Not O.K.	
<b>↓</b>		$\downarrow$	$\downarrow$	$\downarrow$	
	Check tires for damage and condition	$\times$	$\otimes$		AP40.10-P-4051GM
	Measure tread depth, enter in mm:		$\otimes$		AP40.10-P-4051GM
	LF RF LR RR				
	outside				
	center				
	inside				
	Correct tire inflation pressure including	$\boxtimes$	$\otimes$		AP40.15-P-4060G
	spare				
	Vehicle underbody				
	Visual check for: Leakage - Major components		$\otimes$		AP00.20-P-0053AB
	Chafe marks, line routing, damaged				
	components. In the event of leakage,				
	determine cause and perform repair via separate work order.				
	Check condition of front axle joints and rubber bushings		$\otimes$		
			$\otimes$		
			$\otimes$		AP46.00-P-4653G
	Check fluid level, top up if necessary.				
			$\otimes$	П	AP28.00-P-2810G
	Transfer case		8	_	
	Front axle				AP33.10-P-3310G
	Rear axle		$\otimes$		AP35.10-P-3510G
	If loss of fluid present, determine cause and rectify subject to separate repair or- der				
	Lubricate propeller shaft universal joints and collapsible sections	$\boxtimes$	$\otimes$		AP41.10-P-4121G
	Engine compartment				
			Ω		
	Visually check:  Leakage - Major components		$\otimes$	Ц	AP00.20-P-0053AB
	Chafe marks, line routing, damaged				
	components. In the event of leakage,				
	determine cause and perform repair via separate work order.				
	Engine oil and filter change	$\times$	$\otimes$		AP18.00-P-0101GB
	Check and correct fluid level				
	Engine cooling system, antifreeze and corrosion protection °C	$\boxtimes$	⊗		AP20.00-P-2010GA
	<del></del>	×	8		AP29.00-P-2912G
	Brake system	$\boxtimes$	$\otimes$		AP42.50-P-4210G
	•		$\otimes$		AP46.00-P-4611G
	<del>-</del>	X	8	_	ΔP82 35-P-8210G

complete	d⊠	A-Service	□ ↓	○ B-Service	Not O.K.	
		Check condition of poly-V-belt		$\otimes$		AP13.22-P-1351GA
		Lubricate joints on throttle control, check operation and condition		$\otimes$		AP30.10-P-3022G
		Lubricate catch, safety catch and hinges on engine hood	$\boxtimes$	$\otimes$		AP88.40-P-8821G
→(¿())		Front, rear of vehicle				
		Check headlamp aiming, adjust if necessary.		$\otimes$		AP82.10-P-8260G
		Replace windshield wiper rubber inserts		$\otimes$		AP82.30-P-8253G
		Check condition of wiper blade for rear window		$\otimes$		AR82.30-P-6980A
		Additional Work				
complete	ed ⊠ ↓	Perform:	yes ↓		Not O.K. ↓	
		At approx. every 60,000 mi/96,000 km or 4 years:				
<b>⊯</b> AP		Replace air cleaner filter element				AP09.10-P-0980A
₩AP		At approx. every 60,000 mi/96,000 km or 5 years				
		Replace fuel filter				AP47.20-P-0780GA
		Oil change in front axle				AP33.00-P-3301G
		Oil change in rear axle				AP35.00-P-3501G
		Oil change in transfer case				AP28.00-P-2801G
		Every 2 years:				
<b>⊯</b> AP		Replace brake fluid				AP42.50-P-4280G
<b>⊯</b> AP		Check body for paint damage by Service Advisor				AP98.00-P-9850G
		Bolts attaching steering (check/tighten)				AP46.20-P-4671G
<b>⊯</b> AP		Joint housing of AWD front axle - inspect grease packing and correct				AP33.10-P-3321G
		Every 3 years:				
<b>⊯</b> AP		Replace coolant				AP20.00-P-2080GA
₩AP		Sliding/pop-up roof: clean and grease sliding rails and sliders				AP77.20-P-7730G
		Replace spark plugs				
β¥AP		At approx. every 100,000 mi/160,000 km or 5 years				AP15.10-P-1580GA